

## Customary Units

NPS	Outside Diameter (in)	inside diameter (in)	Wall Thickness (in)	Plain End Weight (lb/ft)	Identification [Standard (STD), Extra-Strong (xXS), or Double Extra
1/8	0.405"	0.269"	0.068"	0.24"	STD
1/4	0.540"	0.364"	0.088"	0.43"	STD
3/8	0.675"	0.493"	0.091"	0.57"	STD
1/2	0.840"	0.622"	0.109"	0.85	STD
3/4	1.050"	0.824"	0.113"	1.13"	STD
1	1.315"	1.049"	0.133	1.68"	STD
1 1/4	1.660"	1.380"	0.140"	2.27"	STD
1 1/2	1.900"	1.610"	0.145"	2.72"	STD
2	2.375"	2.067"	0.154"	3.66"	STD
2 1/2	2.875"	2.469"	0.203"	5.8	STD
3	3.500"	3.068"	0.216"	7.58	STD
3 1/2	4.000"	3.548"	0.226"	9.12"	STD
4	4.500"	4.026"	0.237"	10.8	STD
5	5.563"	5.047"	0.258"	14.63	STD
6	6.625"	6.065"	0.280"	18.99	STD
8	8.625"	7.981"	0.322"	28.58	STD
10	10.750"	10.020"	0.365"	40.52"	STD
12	12.750"	11.938"	0.406"	53.57"	---
14	14.000"	13.124"	0.438"	63.50"	---
16	16.000"	15.000"	0.500"	82.85"	XS
18	18.000"	16.876"	0.562"	104.76"	---
20	20.000"	18.812"	0.594"	123.23"	---
24	24.000"	22.624"	0.688"	171.45"	---
32	32.000"	30.624"	0.688"	230.29"	---
34	34.000"	32.624"	0.688"	245.00"	---
36	36.000"	34.500"	0.750"	282.62"	---